

AMENDMENTS TO THE CLAIMS

1. (Previously presented) A method for evaluating a quality of a calibration of an analyte sensor, the method comprising:

receiving a data stream from an analyte sensor, including one or more sensor data points;

receiving reference data from a reference analyte monitor, including one or more reference data points;

providing at least one matched data pair by matching reference analyte data to substantially time corresponding sensor data;

forming a calibration set including said at least one matched data pair;

evaluating a quality of said calibration set using a data association function;

converting sensor data into calibrated data using said calibration set; and

providing the calibrated data to a user interface only when the data association is above a predetermined threshold.

2. (Original) The method of claim 1, wherein the step of receiving sensor data comprises receiving a data stream that has been algorithmically smoothed.

3. (Original) The method of claim 1, wherein the step of receiving sensor data comprises algorithmically smoothing said data stream.

4. (Original) The method of claim 1, wherein the step of receiving sensor data comprises receiving sensor data from a substantially continuous glucose sensor.

5. (Original) The method of claim 1, wherein the step of receiving sensor data comprises receiving sensor data from an implantable glucose sensor.

6. (Original) The method of claim 1, wherein the step of receiving sensor data comprises receiving sensor data from a subcutaneously implantable glucose sensor.

7. (Original) The method of claim 1, wherein the step of receiving reference data comprises receiving reference data from a self-monitoring blood glucose test.

8. (Original) The method of claim 1, wherein the step of receiving reference data comprises downloading reference data via a cabled connection.

9. (Original) The method of claim 1, wherein the step of receiving reference data comprises downloading reference data via a wireless connection.

10. (Original) The method of claim 1, wherein the step of receiving reference data from a reference analyte monitor comprises receiving within a receiver internal communication from a reference analyte monitor integral with said receiver.

11. (Canceled)

12. (Previously presented)The method of claim 1, wherein the step of evaluating a quality of said calibration set based on a data association function comprises performing linear least squares regression.

13. (Canceled)

14. (Previously presented)The method of claim 1, wherein the step of evaluating a quality of said calibration set based on data association comprises performing linear least squares regression and wherein the predetermined threshold is an R-value threshold of 0.79.

15-16. (Canceled)

17. (Previously presented)The method of claim 1, wherein the step of providing calibrated data includes alerting the user dependent upon a quality of said calibration.

18. (Previously presented)The method of claim 1, wherein the step of providing calibrated data includes altering the user interface dependent upon a quality of said calibration.

19. (Previously presented)The method of claim 1, wherein the step of providing calibrated data includes at least one of providing color-coded information, trend information, directional information, and fail-safe information.

20. (Previously presented)A system for evaluating a quality of a calibration of an analyte sensor, the system comprising:

means for receiving a data stream from an analyte sensor, a plurality of time-spaced sensor data points;

means for receiving reference data from a reference analyte monitor, including one or more reference data points;

means for providing one or more matched data pairs by matching reference analyte data to substantially time corresponding sensor data;

means for forming a calibration set including at least one matched data pair;

means for converting sensor data into calibrated data using said calibration set;

and

means for providing calibrated data only when the data association is above a predetermined threshold.

21. (Original) The system of claim 20, wherein said means for receiving sensor data comprises means for receiving sensor data that has been algorithmically smoothed.

22. (Original) The system of claim 20, wherein said means for receiving sensor data comprises means for algorithmically smoothing said receiving sensor data.

23. (Original) The system of claim 20, wherein said means for receiving sensor data comprises means for receiving sensor data from substantially continuous glucose sensor.

24. (Original) The system of claim 20, wherein said means for receiving sensor data comprises means for receiving sensor data from an implantable glucose sensor.

25. (Original) The system of claim 20, wherein said means for receiving sensor data comprises means for receiving sensor data from subcutaneously implantable glucose sensor.

26. (Original) The system of claim 20, wherein said means for receiving reference data comprises means for receiving reference data from a self-monitoring blood glucose test.

27. (Original) The system of claim 20, wherein said means for receiving reference data comprises means for downloading reference data via a cabled connection.

28. (Original) The system of claim 20, wherein said means for receiving reference data comprises means for downloading reference data via a wireless connection.

29. (Original) The system of claim 20, wherein said means for receiving reference data from a reference analyte monitor comprises means for receiving within a receiver internal communication from a reference analyte monitor integral with said receiver.

30. (Original) The system of claim 20, wherein said means for evaluating the quality of said calibration set comprises means for performing one of linear regression, non-linear regression, rank correlation, least mean square fit, mean absolute deviation, and mean absolute relative difference.

31. (Original) The system of claim 20, wherein said means for evaluating the quality of said calibration set comprises means for performing linear least squares regression.

32. (Canceled)

33. (Previously presented)The system of claim 20, further comprising means for evaluating a quality of said calibration set based on a data association function comprising linear least squares regression and wherein said predetermined threshold is an R-value threshold of 0.71.

34-35. (Canceled)

36. (Previously presented)The system of claim 20, wherein said means for providing calibrated data includes means for alerting the user dependent upon a quality of said calibration.

37. (Previously presented)The system of claim 20, wherein said means for providing calibrated data includes means for altering the user interface dependent upon a quality of said calibration.

38. (Previously presented)The system of claim 20, wherein said means for providing calibrated data includes at least one of providing color-coded information, trend information, directional information, and fail-safe information.

39. (Previously presented)A computer system for evaluating a quality of a calibration of an analyte sensor, the computer system comprising:

- a sensor data receiving module that receives a data stream comprising a plurality of time spaced sensor data points from a substantially continuous analyte sensor;

- a reference data receiving module that receives reference data from a reference analyte monitor, including one or more reference data points;

- a data matching module that forms one or more matched data pairs by matching reference data to substantially time corresponding sensor data;

- a calibration set module that forms a calibration set including at least one matched data pair;

- a sensor data transformation module that converts sensor data into calibrated data using said calibration set; and

- an interface control module that displays said calibrated data only when the data association is above a predetermined threshold.

40. (Original) The computer system of claim 39, wherein said sensor data receiving module receives sensor data that has been algorithmically smoothed.

41. (Original) The computer system of claim 39, further comprising a data smoothing module that algorithmically smoothes sensor data received from said sensor data receiving module.

42. (Original) The computer system of claim 39, wherein said sensor data receiving module is adapted to receive sensor data from substantially continuous glucose sensor.

43. (Original) The computer system of claim 39, wherein said sensor data receiving module is adapted to receive sensor data from an implantable glucose sensor.

44. (Original) The computer system of claim 39, wherein said sensor data receiving module is adapted to receive sensor data from subcutaneously implantable glucose sensor.

45. (Original) The computer system of claim 39, wherein said reference data receiving module is adapted to receive reference data from a self-monitoring blood glucose test.

46. (Original) The computer system of claim 39, wherein said reference data receiving module is adapted to download reference data via a cabled connection.

47. (Original) The computer system of claim 39, wherein said reference data receiving module is adapted to download reference data via a wireless connection.

48. (Original) The computer system of claim 39, wherein said reference data receiving module is adapted to receive reference data from a reference analyte monitor integral with said receiver.

49. (Canceled)

50. (Previously presented)The computer system of claim 39, further comprising a quality evaluation module that evaluates a quality of said calibration set based on a data association function comprising a linear least squares regression.

51. (Canceled)

52. (Previously presented)The computer system of claim 39, further comprising a quality evaluation module that evaluates a quality of said calibration set based on a data association function comprising a linear least squares regression and wherein the predetermined threshold of said data association function is an R-value threshold of at least 0.79.

53-54. (Canceled)

55. (Previously presented)The computer system of claim 39, wherein said interface control module alerts the user based upon a quality of said calibration set.

56. (Previously presented)The computer system of claim 39, wherein said interface control module alters the user interface based upon a quality of said calibration set.

57. (Previously presented)The computer system of claim 39, wherein said interface control module provides at least one of color-coded information, trend information, directional information, and fail-safe information.

58. (Canceled)

59. (Previously presented)A method for evaluating a quality of a calibration of an analyte sensor, the method comprising:

receiving analyte sensor data from an analyte sensor;

receiving reference data from a reference analyte monitor;

providing at least one matched data pair by matching reference analyte data to substantially time corresponding sensor data;

evaluating a quality of said at least one matched data pair based on an association of reference analyte data and substantially time corresponding sensor data; and

calibrating the sensor data comprising said at least one matched data pair responsive to the association above a predetermined threshold.

60. (Canceled)

61. (Previously presented)A computer system for evaluating a quality of a calibration of an analyte sensor, the computer system comprising:

a sensor data module configured to receive analyte sensor data from a substantially continuous analyte sensor;

a reference input module configured to receive reference data from a reference analyte monitor;

a processor module configured to form at least one matched data pair by matching reference data to substantially time corresponding sensor data; and

a quality evaluation module configured to evaluate a quality of said at least one matched data pair based on an association of reference data and substantially time corresponding sensor data for said at least one matched data pair, wherein the processor

module is configured to calibrate the sensor data including said at least one matched data pair responsive to the association above a predetermined threshold.

62. (Previously presented) A method for evaluating a quality of a calibration of a glucose sensor, the method comprising:

- receiving sensor data from a glucose sensor, including one or more sensor data points;

- receiving reference data from a reference glucose monitor, including one or more reference data points;

- providing one or more matched data pairs by matching reference glucose data to substantially time corresponding sensor glucose data;

- forming a calibration set including at least one matched data pair;

- evaluating a quality of said calibration set based on a statistical analysis or a clinical acceptability analysis of at least one matched data pair; and

- processing real-time sensor data responsive to the quality of said calibration set above a predetermined threshold.

68-72. (Canceled)

73. (Previously presented) The method of claim 59, wherein the step of evaluating a quality comprises evaluating the association using a statistical analysis.

74. (Previously presented)The method of claim 59, wherein the step of evaluating a quality comprises evaluating the association using a clinical acceptability analysis.

75. (Previously presented)The method of claim 59, further comprising calibrating the sensor data, wherein the step of calibrating is performed during initialization of the analyte sensor.

76. (Previously presented)The method of claim 59, further comprising calibrating the sensor data, wherein the step of calibrating is performed after initialization of the analyte sensor.

77. (Previously presented)The method of claim 59, further comprising calibrating the sensor data, wherein the step of calibrating is performed using a single matched data pair.

78. (Previously presented)The method of claim 59, further comprising calibrating the sensor data, wherein the step of calibrating is performed using more than one matched data pairs.

79. (Previously presented)The method of claim 59, wherein the step of receiving sensor data comprises receiving sensor data that has been algorithmically smoothed.

80. (Previously presented)The method of claim 59, wherein the step of receiving sensor data comprises algorithmically smoothing said sensor data.

81. (Previously presented)The method of claim 59, wherein the step of receiving sensor data comprises receiving sensor data from a substantially continuous glucose sensor.

82. (Previously presented)The method of claim 59, further comprising calibrating the sensor data and displaying a graphical representation of calibrated sensor data.

83-92. (Canceled)

93. (Previously presented)The system of claim 61, wherein the processor module is configured to calibrate sensor data during initialization of the analyte sensor.

94. (Previously presented)The system of claim 61, wherein the processor module is configured to calibrate sensor data after initialization of the analyte sensor.

95. (Previously presented)The system of claim 61, wherein the processor module is configured to calibrate sensor data using a single matched data pair.

96. (Previously presented)The system of claim 61, wherein the processor module is configured to calibrate sensor data using more than one matched data pairs.

97. (Previously presented)The system of claim 61, wherein said sensor data module receives sensor data that has been algorithmically smoothed.

98. (New) The system of claim 61, further comprising a data smoothing module that algorithmically smoothes sensor data received from said sensor data module.

99. (Previously presented)The system of claim 61, wherein said sensor data receiving module is adapted to receive sensor data from a substantially continuous glucose sensor.

100. (Previously presented)The system of claim 61, wherein the processor module is configured to calibrate sensor data, and further comprising an output module configured to display calibrated sensor data.

101. (Previously presented)The system of claim 61, wherein the quality evaluation module is configured to evaluate the association using a statistical analysis.

102. (Previously presented)The method of claim 61, wherein the quality evaluation module is configured to evaluate the association using a clinical acceptability analysis.

103. (Previously presented)The method of claim 62, further comprising calibrating sensor data, wherein the step of calibrating is performed during initialization of the glucose sensor.

104. (Previously presented)The method of claim 62, further comprising calibrating sensor data, wherein the step of calibrating is performed after initialization of the analyte sensor.

105. (Previously presented)The method of claim 62, further comprising calibrating the sensor data, wherein the step of calibrating is performed using a single matched data pair.

106. (Previously presented)The method of claim 62, further comprising calibrating sensor data, wherein the step of calibrating is performed using more than one matched data pairs.

107. (Previously presented)The method of claim 62, wherein the step of receiving sensor data comprises receiving sensor data that has been algorithmically smoothed.

108. (Previously presented)The method of claim 62, wherein the step of receiving sensor data comprises algorithmically smoothing said sensor data.

109. (Previously presented)The method of claim 62, wherein the step of receiving sensor data comprises receiving sensor data from a substantially continuous glucose sensor.

110. (Previously presented)The method of claim 62, further comprising calibrating sensor data and displaying a graphical representation of the calibrated sensor data.